

ESR-208

Build Unique Storage Solutions with a Technology Edge

The ESR 208 is a EIA310-D standard 2U chassis designed that balances what is possible and what is needed. It supports most form factor server board in the market, From Single Pentium 4 or AMD Althon, Dual Intel Nocona/Irwindale or Dual AMD Opteron Server Boards in a high density and cost-effective enclosure. The ESR-208 storage server chassis deliver technology that differentiates your company by helping you to create integrated competitive solutions that win. Your customers need it, expect it, and demand it



The ESR series Storage server balances what the End-User and System vendor needs to deliver the best solution, provides classy design, highest flexibility, easy to install and maintain, more storage in limited space and ultimate drive and data protection in this limited space. Each unit has up to six hot-swappable cooling fans and with multiple temperature sensors at the hot points. The ESR-208 redundant, load-sharing power supply modules and power management circuitry accommodate the dynamic requirements of today's drives. ESR-208 further includes power supply-to-drive isolation, which allows control over voltage and current fluctuations

Chassis Specification

1. EIA 310-D standard 2U chassis, Dimension 19"Wx3.42"Hx28"D
2. Corrosion-resistant steel construction
3. Includes 8Hot Swappable, low-profile hard-disk drive carriers with dual status LEDs at each drive carrier
4. Support Ultra 320, SATA, and SAS
5. Support SSI CEB1.0, SSI EEB 3.5, extended ATX form factor
6. Support Low Profile Backpanel or 3 tier Backpanel
7. On board temperature sensors
8. On board enclosure management feature includes multiple temperature sensors with audible and visible alarm, Power Supply health audible and visible alarm, System fan health audible and visible alarm
9. Front Panel includes:
 - Buttons and Switches: Power on/off (momentary) button, system-reset button, alarm reset button
 - LEDs: Power, Hard-Disk activity, network activity (two), system health
 - Connectors: Two USB ports, One serial port
10. Support up to 6 hot-swap 80mm high speed fans for system cooling that can be connected to system board to provide RPM control and data for fan-failure prediction and detection
11. Support up to 3 x 2.5" internal slim hard-disk drives
12. Includes slim CD-Rom and slim FDD carriers and conversion board
13. Fixed or 1+1 Redundant Power Supply with simple cable connection
14. Power Supply Option: 350W for Single CPU, 460W for Dual Opteron and 550W for Dual Xeon Nocona/Irwindale system
15. Horizontal BP design for better airflow, provides space for future SAS edge expander chips and delivers efficient connectivity to larger number of devices
16. Optional mechanical lock front bezel (special order only)
17. Includes easy install Slide-Rail Kit

SATA Backplane Specification

1. A power MOSFET to provide disk spin-up control
2. A pre-charge circuit for surge current protection when a disk is plugged in to protect the hard-disk drive and the backplane.
3. LED: Blue ON = HDD present; Blue Blanking = Drive activity; Red=Drive failed
4. A 4x2 header for Drive activity and Drive failed LED signal input
5. A 4x3 jumper with 4 jumper cap is added to select either disk activity LED is provide by the Host Bus Adapter or form HDD such as Western Digital or Maxtor Diamond Max X hard disk drive
6. Single DC input to provide better cable management
7. SATA data connector with latch to secure the SATA cable is not loose
8. Options included Point-to-Point or Multilane data cable connection. 32pin 4-lane-to-1-lane connection available (special order only)

SCSI Backplane Specification

1. A power MOSDET to provide disk spin-up control
2. A pre-charge circuit for surge current protection when a disk is plugged in to protect the hard-disk drive and the backplane.
3. LED: Blue ON = HDD present; Blue Blanking = Drive activity; Red=Drive failed
4. A 4x2 header for Drive activity and Drive failed LED signal input
5. Single DC input to provide better cable management
6. Piano Switch for easy SCSI ID setting
7. Two HD68 SCSI connectors for daisy chain if required